



CP10M0N0

BAKERY OVEN 10 TRAYS 600x400 - GN 1/1
MECHANICAL CONTROL

FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Electric
Timer	Linear scale
Number of motors	3
Motor speeds	1
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50mm open
Humidification	Direct injection
Air injection	-
Self-washing	Standard



STANDARDS	
Cer tification	CE
TRAYS	
Trays rack	Wire PA-BIV 10/80 mm
Max tray load	4kg
DIMENSIONS	
Oven size with handle WxDxH	818 x 893 x 1318,4 mm
Oven size without handle WxDxH	818 x 827,5 x 1318,4 mm
Chamber size WxDxH	660 x 490 x 948 mm
Unit weight	128kg
PACKAGING	
Packaging	Pallet + carton box
Packaging size WxDxH	895 x 970 x 1460 mm
Unit weight with packaging	144kg
ELECTRICAL DATA	
HEATERS 5kW 50/60Hz	
Power	15,8kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	25,2A
Power cord req.	5G4
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa
CONSUMPTION	
Humidification Water	22,4l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-



CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA8274H17X - TA8274H30X TA8274H40X - TA8274H40S TA8274H49X - TA8274H49S TA8274H70X - TA8274H70S TA8274H80X - TA8274H80S
Stand wheel kit	R100
Hood (Air)	-
Hood (Water)	POCPMWF1 - POCPMWF2
External Core probe	-
Sous vide probe	-
Proofer	-
Stacking kit for 2 ovens	SKCP66
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800l	WS11
Water softner 12000l	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6kg	DT2
Detergent 10kg	DT4



◆ Standard ◇ Optional - Not available

TYPE OF COOKINGS

Convection cooking	30°C - 260°C - 86°F - 500°F
Combi cooking	30°C - 230°C - 86°F - 446°F
Steaming cooking	30°C - 130°C - 86°F - 266°F -
Static cooking	-
Delta T cooking	-
Core probe cooking	-
Sous vide cooking	-
Low temperature cooking	

DISPLAY AND CONNECTIVITY

Type of display	ANALOGIC
Multi-language display	-
Unit set F° or C°	◇
Venix cloud	-
Wi-fi	-
Ethernet port	-
Web server	-
Usb port	-

SETTINGS

Infinity time set	◆
Chimney set	OPEN
Fan speed set	1/2
Dehumidification set	-
Humidity set	0-100%
Preheat set	MANUAL

RECIPE COOKING

User recipes book	-
Factory recipes book	-
Cooking cycles	-
Recipes with name and picture	-
Fast recipe selection buttons	-

SPECIAL CYCLE

Multi-level mix ALL IN	-
Multi-level mix ALL OUT	-
Food regeneration	-
Overnight cooking	-
Overnight self clean	-
Cook & hold	-



+9714 2 88 2777 admin@mariotkitchen.com

www.mariotstore.com







Multi-timer	-
Routine program	-
Proofing	-
Fast Cooling	-
Automatic washing system / Rinse	-
Fast start	-
Recipe scheduling	-
Holding / Mass production	-

TECHNICAL FEATURES

Cooking chamber material	AISI304
Second core probe	-
Insertion of the trays	HORIZONTALLY
Fast loading Pro	-
Glass door	DOUBLE
Easy clean internal glass	◆
High performance thermal insulation	YES
Break drop nebulizer	◆ FIXED ON THE DOOR
Lightning	◆ NOT REVERSIBLE (RIGHT HANDLE)
Direct injection humidification	◆
Boiler humidification	
Opening door	
Reversing fan	
Heavy duty reversing fan	
Phase cut speed control	-
Inverter speed control	-





01. TIMER SELECTOR
02. LIGHT ON/OFF HEATING ELEMENT
03. TEMPERATURE SELECTOR
04. STEAM LED
05. STEAM SELECTOR
06. DOUBLE SPEED BUTTON (only if provided)
07. HOT VAPOUR CHIMNEY Ø50MM (1,97")

08. SAFETY THERMOSTAT
09. UNIPOTENTIAL TERMINAL
10. COMPRESSION CABLE GLAND
11. DRAIN PIPE Ø30MM (1,18)
12. WATER IN-LET SOLENOID VALVE G3/4" (HUMIDIFICATION)



+9714 2 88 2777 admin@mariotkitchen.com

www.mariotstore.com

