



T04MIHAER

CONVECTION OVEN 4 TRAYS 600X400 - GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	MECHANICAL
Supply	ELECTRIC
Timer	LINEAR
Number of motors	2
Motor speeds	1 speed + reverse rotation
Max cooking temperature (°C)	260
Probe	-
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-GA 4/75
Max tray load	3Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	750 x 693 x 553
Oven size without handle WxDxH (mm)	750 x 645 x 553
Chamber size WxDxH (mm)	660 x 456 x 340
Unit weight (Kg)	45

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	774 x 764 x 682
Unit weight with packaging (Kg)	50
Crate packaging size (optional)	-

ELECTRICAL DATA

Heaters 3.1kW 50/60 Hz	
Power	6,7kW
Frequency	50/60 Hz



Power supply	380-415V 3N~/220-240V 3~/220-240V ~
Amperage	13,5A / 23,4A / 29,12A
Power cord req.	5G1,5/ 4G4/ 3G6

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas Threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5° f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water with solenoid valve	0.8l/min max consumption
Humidification Water with pump	0.05l/min max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA8058H60X - TA8058H60S TA8058H80X - TA8058H80S
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	POCK
Core Probe	-
Proofer	CA8008M0 CA8008MH CA8008DH
Stacking kit for 2 ovens	SKTC04N00



Smoker	-
Blast Chiller	ASP05 KDA03 KDA05
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6 Kg	-
Detergent 10 Kg	-
Air reducer	RID07

