



S Q20TCC

COMBI OVEN 20 TRAYS - GN 1/1
5" CAPACITIVE TOUCH CONTROL
SELF CLEANING INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	5" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	4
Motor speeds	2
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm motorized
Humidification	Direct injection
Air injection	-
Self-washing	Automatic

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Trolley PA 20/66
Max tray load	4 Kg

DIMENSIONS

Oven size with handle WxDxH (mm)	1051x1002x1900
Oven size without handle WxDxH (mm)	1051x938x1900
Chamber size WxDxH (mm)	700x481x1496
Unit weight (Kg)	250

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1150 X 1100 X 2050
Unit weight with packaging (Kg)	273
Crate packaging size (optional)	1100 x 1150 x 2090
Unit weight with crate (Kg)	331



ELECTRICAL DATA

HEATERS 6,75kW 50Hz - Single power supply

Power	28,1kW
Frequency	50Hz
Power supply (standard)	380 - 415V 3N~
Amperage (standard)	43,9A
Power cord req. (standard)	5G10

HEATERS 6,75kW 50Hz - Double power supply

Power	28,1kW
Frequency	50Hz
Power supply (optional)	380 - 415V 3N~/220 - 240V 3~
Amperage (optional)	43,9A/71,9A
Power cord req. (optional)	5G10/4G25

HEATERS 6,75kW 60Hz - Single power supply

Power	28,7kW
Frequency	60Hz
Power supply (standard)	380 - 415V 3N~
Amperage (standard)	46,5A
Power cord req. (standard)	5G10

HEATERS 6,75kW 60Hz - Double power supply

Power	28,7kW
Frequency	60Hz
Power supply (optional)	380 - 415V 3N~ /220 - 240V 3~
Amperage (optional)	46,5A/74,1A
Power cord req. (optional)	5G10/4G25

HEATERS 5kW 50Hz

Power	25,7kW
Frequency	50Hz
Power supply	440V 3~
Amperage	36,7A
Power cord req.	4G10



HEATERS 5kW 60Hz	
Power	26,2kW
Frequency	60Hz
Power supply	440V 3~
Amperage	39,3A
Power cord req.	4GX10

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS
Washing Water Inlet	10 mm quick fitting
Water drain	2x30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	16,7l/h max consumption
Rinse Water @2barG	35,5l
Short Washing Water @2barG	66,6l
Long Washing Water @2barG	139l
Short Washing Detergent *	468,8g
Long Washing Detergent *	669,7g

CONNECTIVITY

USB	2.0
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	POSLMWF1 POSLMWF2
Core Probe	-
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast Chiller	-



Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4



+9714 2 88 2777 admin@mariotkitchen.com

www.mariotstore.com

