

## Electric Induction Cooker

18/10 AISI 304 Stainless Steel | 3500 W

TSCL-002 | 220 V / 50 Hz | 50-300 °C



### KEY SPECIFICATIONS

Electric Induction Cooker

|             |                    |
|-------------|--------------------|
| Model       | TSCL-002           |
| Temperature | 50-300 °C          |
| Power       | 3500 W             |
| Voltage     | 220 V              |
| Frequency   | 50 Hz              |
| Weight      | 8 kg               |
| Steel       | 18/10 AISI 304     |
| Finish      | Scotch Brite       |
| Dimensions  | 400 x 500 x 250 mm |

### ELECTRIC INDUCTION

3500 W rated power  
220 V / 50 Hz supply  
Scotch Brite finish

### TSCL-002 Electric Induction Cooker

3500 W | 220 V / 50 Hz | 400 x 500 x 250 mm

50-300 °C temperature range | Weight: 8 kg

18/10 AISI 304 stainless steel with a Scotch Brite finish.

Product Details

TSCL-002 | Electric Induction Cooker

FEATURES

- Electric induction cooker.
- Temperature range: 50-300 °C.
- Rated power: 3500 W.
- Electrical supply: 220 V / 50 Hz.
- 18/10 AISI 304 stainless steel construction.
- Scotch Brite finish.
- Weight: 8 kg.

TECHNICAL SPECIFICATIONS

|                   |                                |
|-------------------|--------------------------------|
| Model             | TSCL-002                       |
| Product type      | Electric induction cooker      |
| Temperature range | 50-300 °C                      |
| Rated power       | 3500 W                         |
| Voltage           | 220 V                          |
| Frequency         | 50 Hz                          |
| Weight            | 8 kg                           |
| Construction      | 18/10 AISI 304 stainless steel |
| Finish            | Scotch Brite                   |
| Dimensions        | 400 x 500 x 250 mm             |

PRODUCT OVERVIEW

The TSCL-002 electric induction cooker is rated at 3500 W and operates on a 220 V / 50 Hz supply. Temperature range: 50-300 °C. 18/10 AISI 304 stainless steel construction with a Scotch Brite finish. Weight: 8 kg. Dimensions: 400 x 500 x 250 mm.