

Single Door Upright Freezer

700 L Capacity | -25°C to -10°C | 500 W

PBB7 | DESMON | Italy



KEY SPECS

COMMERCIAL UPRIGHT FREEZER

Model	PBB7
Capacity	700 L
Temperature	-25 to -10°C
Shelves	3
Refrigerant	R290 / 70 g
Absorbed power	500 W
Net weight	125 kg
Dimensions	720 x 798 x 2120 mm

PROFESSIONAL FREEZING

The DESMON PBB7 is a 700 L stainless steel upright freezer with a monoblock refrigeration system, digital controller and three epoxy-coated wire shelves.

DESMON PBB7 | Single Door Upright Freezer

Overall dimensions (W x D x H): 720 x 798 x 2120 mm

Temperature range: -25°C to -10°C | Capacity: 700 L

Product Features & Technical Specifications

PBB7 | DESMON Single Door Upright Freezer

KEY FEATURES

- 700 L single-door upright freezer for professional kitchens.
- Stainless steel interior and exterior construction.
- Monoblock refrigeration system and electronic digital controller.
- Three standard epoxy-coated wire shelves.
- Embossed, hinged front panel for routine maintenance.
- Adjustable stainless steel legs; locking casters available as an option.
- Power cord and Schuko 16 A plug included.

TECHNICAL SPECIFICATIONS

Model	PBB7
Product	Single door upright freezer
Brand / Country of origin	DESMON / Italy
Gross capacity	700 L
Door configuration	Single hinged door
Construction	Stainless steel interior and exterior
Supplied shelves	3 epoxy-coated wire shelves
Temperature range	-25°C to -10°C
Refrigeration system	Monoblock
Refrigerant / charge	R290 / 0.070 kg (70 g)
Controller	Electronic digital controller
Front panel	Embossed, hinged for maintenance
Legs / option	Adjustable S/S legs / locking casters optional
Absorbed power	500 W (0.5 kW)
Electrical supply	220 V / 50 Hz / 1 Ph
Rated current	2.5 A
Plug	Schuko 16 A (cord and plug included)
Net weight	125 kg
Dimensions (W × D × H)	720 × 798 × 2120 mm
Packing dimensions (W × D × H)	780 × 860 × 2280 mm

PRODUCT OVERVIEW

The DESMON PBB7 is an Italian-made commercial upright freezer designed for professional foodservice. It provides 700 L capacity, a -25°C to -10°C operating range, stainless steel construction and convenient digital control. Three epoxy-coated wire shelves are supplied as standard.