

Two-Door Upright Refrigerator

1400 L Capacity | -2°C to +8°C | 400 W
PBM14 | DESMON | Italy



KEY SPECS	
UPRIGHT REFRIGERATOR	
Model	PBM14
Capacity	1400 L
Doors / shelves	2 / 6
Temperature	-2 to +8 °C
Rated power	400 W
Refrigerant	R290 / 0.062 kg
Net weight	185 kg
Dimensions	1440 x 798 x 2120 mm
PROFESSIONAL COOLING	
The DESMON PBM14 provides 1400 L of refrigerated storage with a digital controller, stainless steel construction and a monoblock refrigeration system for commercial kitchens.	

DESMON PBM14 | Commercial Two-Door Upright Refrigerator

Overall dimensions (W x D x H): 1440 x 798 x 2120 mm
Temperature: -2 to +8 °C | Capacity: 1400 L

Product Features & Technical Specifications

PBM14 | DESMON Commercial Two-Door Upright Refrigerator

KEY FEATURES

- 1400 L total capacity with two-door upright configuration.
- Stainless steel interior and exterior construction.
- Six shelves for organized refrigerated storage.
- Monoblock refrigeration system.
- Embossed, hinged front panel for routine maintenance access.
- Electronic digital temperature controller.
- Adjustable stainless steel legs; optional locking casters.
- Power cord and Schuko 16 A plug included.

TECHNICAL SPECIFICATIONS

Model	PBM14
Product type	Two-door upright refrigerator
Brand / origin	DESMON / Italy
Capacity	1400 L
Door configuration / shelves	2 doors / 6 shelves
Cabinet construction	Stainless steel interior and exterior
Temperature range	-2 °C to +8 °C
Refrigeration system	Monoblock
Refrigerant / charge	R290 / 0.062 kg
Temperature controller	Electronic digital
Front panel	Embossed hinged panel
Legs / optional casters	Adjustable S/S legs / locking casters optional
Electrical supply	220 V / 50 Hz / 1 phase
Plug / connection	Schuko 16 A / cord and plug included
Absorbed power / current	400 W / 2.2 A
Net weight	185 kg
Dimensions (W x D x H)	1440 x 798 x 2120 mm
Packing dimensions (W x D x H)	1480 x 860 x 2280 mm

PRODUCT OVERVIEW

The DESMON PBM14 is a commercial two-door upright refrigerator designed for professional food-service environments. With 1400 L storage capacity and a -2°C to +8°C operating range, it combines stainless steel construction, six shelves, digital temperature control and a monoblock refrigeration system. The hinged embossed front panel facilitates routine maintenance.