MARIOT®
KITCHEN EQUIPMENT

PRODUCT DATA SHEET
GFT66L

Countertop Gas Griddle - Smooth Plate

2 Heating Zones | Gas Heating | AISI 304 Stainless Steel
GFT66L | MBM | Italy



KEY SPECS

Model	**GFT66L**
Surface	**Smooth plate**
Burner layout	**2 x 5.1 kW**
Listed gas power	**12 kW***
Plate size	**600 x 510 x 12 mm**
Net / gross	**59 / 62 kg**
Overall size	**600 x 600 x 270 mm**

COMMERCIAL COOKING

Smooth countertop gas griddle with welded splash guard, front grease channel, removable liquid collection drawer, and pilot-flame protection.

MBM GFT66L | Smooth Gas Griddle

Overall dimensions (W x D x H): 600 x 600 x 270 mm
Cooking plate: 600 x 510 mm | Thickness: 12 mm
Burner layout: 2 x 5.1 kW = 10.2 kW | Net / gross: 59 / 62 kg

* Listed gas power is 12 kW, while burner layout totals 10.2 kW; verify rating.
ISO 9001 and Italy origin are supplied references; not independently verified.

Product Features & Technical Information

GFT66L | MBM | Countertop Smooth Gas Griddle

KEY FEATURES

- Smooth cooking plate for direct-contact grilling
- Two 5.1 kW heating zones as stated in the supplied layout
- Welded splash guard and front grease-collecting channel
- Removable drawer for collected cooking liquids and grease
- High-quality AISI 304 stainless-steel construction
- Pilot-flame protection and panel support
- 12 mm thick cooking plate

DETAILED TECHNICAL SPECIFICATIONS

Brand / manufacturer	MBM
Model	GFT66L
Equipment type	Countertop gas griddle
Cooking surface	Smooth plate
Burner layout	2 x 5.1 kW = 10.2 kW
Gas power (listed)	12 kW - verify discrepancy
Worktop / body	AISI 304 stainless steel
Cooking plate (W x D)	600 x 510 mm
Cooking plate thickness	12 mm
Splash protection	Welded splash guard
Grease collection	Front channel + removable drawer
Flame protection	Pilot flame
Net / gross weight	59 kg / 62 kg
Overall dimensions	600 x 600 x 270 mm
Country of origin	Italy (supplied)
Quality reference	ISO 9001 (supplied; unverified)

INSTALLATION & VERIFICATION NOTES

Listed gas power (12 kW) differs from the burner layout total (10.2 kW); verify rated input.

Gas type, inlet pressure, connection size and clearances were not supplied; consult MBM instructions.